

MS-9A08 Barebone

Intel® 45nm Core™ 2 Duo Embedded System

Anwendungsgebiete



Digital Signage



Prozessregelung



Kiosk



POS/ Retail



Entertainment



Gaming



Geldautomat



Klinischer Bereich

MS-9A08 Barebone

- Intel® 45nm Core™ 2 Duo design with small dimension chassis
- Multiple Video Output: HDMI, DVI and VGA with dual independent display
- Support DirectX 10®, Shader Model 4.0 und Intel® Clear Video Technology



MSI Artikelnummer		009A08-010R
MKT Name		MS-9A08 Barebone
Prozessor	CPU	Support Intel® Core™ 2 Duo
	Chipsatz	Intel® Mobile GM45 Express chipset + ICH9M-E
Speicher	Technologie	Dual channel DDR2 533/667/800 MHz
	Max. Kapazität	Bis zu 4 GB
	Socket	2 x 200-pin SODIMM
Display	Grafik	Intel® Graphics Media Accelerator (GMA) 4500MHD
	LVDS	Support single and Dual Channel 18,24-bit. Resolution up to 1920x1200 (WUXGA)
	DVI	Chrontel CH7318C SDVO Transmitter-Resolution: Bis zu 1920 x 1080 (1080P)
	HDMI	Support HDMI 1.3, Type A,19-pin
	Dual Display	CRT+DVI, CRT + HDMI
Ethernet	Controller	LAN1: Intel 82567LM GbE LAN, LAN2: Intel 82574L GbE LAN
Audio	Controller	Realtek ALC888 HD audio codec (Line-in,Line-out, Mic-in)
I/O Interface	USB	6x USB 2.0
	Seriell	3x RS232 Front, unterstützt 5V/12V 1x RS232/485/422 Rear, unterstützt 5V/12V
Erweiterung	Mini-PCI	1 slot
	PCI	32-bit/33MHZ, 1 slots
Speicher	SATA	4x SATA II (1x für 2,5" HDD) , Default 160 GB, Max. transfer rate 3Gb/s
Support		Windows® XPP/ XPE
Power	Power Adaptor	DC 19V, 90W
	Power Supply	N/A
Umweltbedingungen	Betriebstemperatur	0°C - 40°C
	Lagertemperatur	-20°C - 70°C
	Betriebsfeuchtigkeit	0% - 90% relative Feuchtigkeit, nicht kondensierend
	Lagerfeuchtigkeit	0% - 90% relative Feuchtigkeit, nicht kondensierend
Gehäuse	Abmessungen	180 mm x 180mm x 44 mm
	Gewicht	1,07 kg
	Befestigung	VESA Mount
Gesetzliche Bestimmungen		FCC, CE, C-tick, BSMI, VCCI, RoHS Compliant

